

SURGE PROTECTOR



PA-GEJ-01SDL

Max.3500W 230V~
SPD TYP 3
Response Time <1 nanosecond
L-E:12500A;L-N 12500A;N-E 12500A
Clamping Voltage 2.5KV
Joule Rating 2000J
Maximum Spike Current 37500A
With photosensitive light



PA-GEJ-01SD

Max.3500W 230V~
SPD TYP 3
Uc=250V
Uoc:2.5KV(L-N)5.0KV(L/N-PE)
Up:1.6KV(L-N)1.3KV(L/N-PE)



PA-GE3A-01SD

Max.3500W 230V~
SPD TYP 3
Uc=250V
Uoc:2.5KV(L-N)5.0KV(L/N-PE)
Up:1.8KV(L-N)2.5KV(L/N-PE)



PA-FR3-01SD

Max.3500W 230V~
SPD TYP 3
Uc=250V
Uoc:2.5KV(L-N)5.0KV(L/N-PE)
Up:1.8KV(L-N)2.5KV(L/N-PE)



PA-GE1-01SD1

Max. 3500W 230V~
Time delay 3-5 minutes
SPD TYP 3
Uc=250V~
Uoc: 5KV(L-N)/4KV(L/N-PE)
Up: 2.0KV(L-N,L/N-PE)



PA-GEA-01SD

Max.3500W 230V~
SPD TYP 3
Uc=250V~
Uoc: 5KV(L-N)/4KV(L/N-PE)
Up: 2.0KV(L-N,L/N-PE)