

Oscillator (CMOS/LVPECL/LVDS/HCSL Output)

4.1 XO3225

3.2 x 2.5 mm SMD
Crystal Oscillator



FEATURES

- Typical 3.2 x 2.5 x 0.95mm Ceramic SMD Package
- Tight Symmetry (45 to 55%) Available
- Operation Voltage: 1.8V, 2.5V, 3.3V
- Tri-State Enable/Disable Operation

TYPICAL APPLICATION

- WLAN/WiMAX
- Mobile Phone
- DSC, Set-Top Box, HDTV

DIMENSIONS



Pin Connection

Name	Connection
pin 1	Tri - State
pin 2	GND
pin 3	Fout
pin 4	Vdd

ELECTRICAL SPECIFICATION

Parameter		3.3V		2.5V		1.8V		Unit
		Min.	Max.	Min.	Max.	Min.	Max.	
Supply Voltage Variation (VDD)		VDD-5%	VDD+5%	VDD-5%	VDD+5%	VDD-5%	VDD+5%	V
Frequency Range		1.25	125	1.25	125	1.25	125	MHz
Standard Frequency		24, 26, 30, 40						MHz
Supply Current	At 15pF Load	—	15	—	10	—	7	mA
	No Load Condition, $1.25\text{MHz} \leq F_o < 10\text{MHz}$	—	1.5	—	1.5	—	1.2	mA
	No Load Condition, $10\text{MHz} \leq F_o < 20\text{MHz}$	—	2	—	2	—	1.5	mA
	No Load Condition, $20\text{MHz} \leq F_o < 80\text{MHz}$	—	3	—	2.5	—	1.5	mA
	No Load Condition, $80\text{MHz} \leq F_o < 125\text{MHz}$	—	8	—	7	—	5	mA
Duty Cycle		45	55	45	55	45	55	%
Output Level	Output High	2.97	—	2.25	—	1.62	—	V
	Output Low	—	0.33	—	0.25	—	0.18	
Transition Time: Rise/Fall Time+	$1.25\text{MHz} \leq F_o < 10\text{MHz}$	—	3	—	4	—	5	nSec
	$10\text{MHz} \leq F_o < 20\text{MHz}$	—	3	—	3	—	4	nSec
	$20\text{MHz} \leq F_o < 80\text{MHz}$	—	3	—	3	—	4	nSec
	$80\text{MHz} \leq F_o < 125\text{MHz}$	—	3	—	3	—	4	nSec
Startup Time		—	2	—	2	—	2	mSec
Tri-State (Input to Pin2 or Pin1)	Enable (High Voltage or Floating)	2.31	—	1.75	—	1.26	—	V
	Disable (Low Voltage or GND)	—	0.99	—	0.75	—	0.54	
Output Loading		15		15		15		pF
Stand by Current	(@-40 ~ 85°C)	—	10	—	10	—	10	uA
	(@-40 ~ 125°C)	—	20	—	20	—	20	uA
Aging (@25°C, 1st Year)		—	±3	—	±3	—	±3	ppm
Storage Temp. Range		-55	125	-55	125	-55	125	°C
Period Jitter(Pk-Pk)		—	40	—	40	—	40	pSec
RMS Phase Jitter(Integrated 12 KHz ~ 20MHz)		—	1	—	1	—	1	pSec



Oscillator (CMOS/LVPECL/LVDS/HCSL Output)

FREQ. STABILITY vs. TEMP. RANGE

Temp.(°C)	ppm	±20	±25	±50
-10 ~ +60		○	○	○
-20 ~ +70		△	○	○
-40 ~ +85		×	○	○

*○: Available △: Condition X: Not available

*Inclusive of calibration @ 25 °C, operating temperature range, input voltage variation, load variation, aging (1st year), shock, and vibration.

Note: not all combination of options are available. Other specifications may be available upon request.
Specifications subject to change without notice.